

SPECIFICATION

Product number: G22BYK20-S01

Product type: Square screen display



| | | |
|------------------|--------------|----------------|
| | | |
| Checked by | Rechecked by | Approved by |
| | | |
| | | |
| Comments | Approved by | Company's seal |
| | | |
| Customer's Name: | | |

Please send the original back to us after you have approved and signed.

Modify History

| Ver. | Page | Revised Descriptions | Date | Revision | Approval |
|---------|------|----------------------|------------|----------|----------|
| REV.1.0 | ALL | T0 | 2026.01.12 | | |
| | | | | | |
| | | | | | |

Product Parameter:

| 22" | | Model | Specifications | Units/Number | Notes |
|-------------------|-----------------------|-------|---------------------------|-------------------|-------|
| | Dimension | | 412.4 (L)*412.4(H)x30(W) | MM | |
| | Shell material | | Black fine sand texture | - | |
| | Gross Weight | | / | Kg/gross | |
| Screen Parameters | Display Size | | 394.56(L)x 394.56(H) | MM | |
| | Display- resolution | | 1920*1920 | Pixel | |
| | Brightness | | 500 | Cd/m ² | |
| | Contrast ratio | | 1000:1 | - | |
| | Display scale | | 1:1 | - | |
| | Viewing angle | | 89/89/89/89 (Typ.)(CR≥10) | - | |
| | Pixel pitch | | 0.2055*0.2055 | MM | |
| | Display color | | 16.7M , 72% NTSC | M | |
| Electrical | Maximum power | | ≤40 | W | |
| | Standby power | | ≤1 | W | |
| | Supply Voltage | | 12V | V | |
| | Horn | | 3W/8 Ω*2 | - | |
| WorkStorage | Operating temperature | | 0-50 | °C | |
| | Working- humidity | | 10% ~80% | %hr | |
| | Storage temperature | | -20-50 | °C | |
| | Storage Humidity | | 10% ~80% | %hr | |
| Power interface | | | DC 12V 5A | | |

| <div> <div>22"</div> <div>Model</div> </div> | | Specifications | Units/Number | Notes |
|--|-----------------------|--|--------------|-------|
| Functional configuration | CPU | RK3568, quad-core processor with a maximum clock speed of 2.0GHz | | |
| | Operating System | Android 11 | | |
| | Memory Storage | Standard 2G+32G / optional 4G+32G/8G+64G | | |
| | built-inROM | / | | |
| | HDMI Out | / | | |
| | HDMI import | 1*HDMI IN | | |
| | Support Video-Formats | Supports wmv, avi, flv, rm, rmvb, mpeg, ts | | |
| | Support Image-Formats | Supports BMP, JPEG, PNG, GIF | | |
| | Audio Input/Output | Supports left and right channel output, with built-in dual 4R/20W and 8R/10W power amplifiers | | |
| | Headphone Output | support | | |
| | USB Interface | 1*USB 3.0 HOST/1*USB 3.0 OGT | | |
| | Serial Port | 1*RJ45 | | |
| | Network Support | Supports Gigabit Ethernet, 2.4G/5G dual-mode Wi-Fi, 6th generation wireless technology (Wi-Fi 6), and 802.11 a/b/g/n/ac/ax protocols. Also supports Bluetooth 5.0. | | |
| | Memory Card | Supports TF cards | | |
| | RTC | Built-in real-time clock | | |
| | System Upgrade | Supports OTA remote upgrades and USB flash drive upgrades | | |

Product Rendering:



Product Dimension Drawing:

